
BluCHIP 4R/16I/12O-E4M1L



BluCHIP 4R/16I/12O-E4M1L

Mercury MR52 Four Reader/Sixteen Input/Twelve Output Addition System w/ Managed Lock Power for Eight Doors

The BluCHIP 4R/16I/12O-E4M1L is a unified Four Reader/Sixteen Input/Twelve Output Addition Sytem w/ Managed Lock Power for Eight Doors and expansion space to support four additional readers. TThe kit is configured with space to add backup battery and utilizes an FPO power supply to generate 24VDC and a B100 to generate 12VDC. It includes two Mercury MR52 boards, a locking eight door enclosure with tamper, power supply and wiring speed kit. It is expandable to eight readers with two Mercury MR52 boards. Local managed lock power is included. Remote management and reporting of power supply and battery health are available through BluSKY Power Diagnostics.



System Features

FPO offline power supply

- 120 or 230 VAC input
- 12 and 24 VDC outputs
- On board Fire Alarm Interface
- Continuous and resettable DC

Distributed output module

- Four, controlled fused at 3A each
- Eight, auxiliary Class II P limited at 2.5A each

Expansion options

- Increased power, multiple voltages
- Additional distribution outputs
- Power management

Specifications

Input Power:

- Input 120/230VAC 50/60Hz | 200 Watts
- Overload and short circuit protection
- Over temperature protection
- Polarized AC power supply disconnect

Output Power:

- 150W Total Output Power | 12VDC/12A or 24VDC/6A
- 5-18VDC @ 4A Max. | FPO Board Outputs: Continuous (DC1), Resettable (DC2)
- 8 Lock Outputs, 8 Auxiliary Outputs, Class 2 PL @ 2.5A each
- 120mV Output Voltage Ripple | System Efficiency: 88% | System BTU Rating: 66 BTU/Hr

Battery Charging:

- Independent built-in 2A (FPO150) Charger for sealed leadacid or gel type batteries
- Microprocessor dual rate charging of 12 or 24V battery sets
- Automatic switchover to standby battery when AC fails
- Zero voltage drop when switched over to battery backup

Enclosure Features Labor saving design

- Unified power and security in one enclosure
- Pre-wired power section
- Removeable backplate simplifies installs
- Speed kit is included for power and data wiring
- Includes mounting studs on door to add additional I/O boards

Additional benefits

- Wire management room
- 4.5" enclosure depth fits battery set
- Tamper switch, lock, dual key set standard
- Mounting hardware for access boards included

Regulatory Compliance:

• UL294, UL603, UL864, UL1076, UL1481, UL2044, UL2572, ULC S318, ULC S319, ULC S527, CSA C22.2 #107.1, FCC Part 15, CSFM Approved

Access Panel:

• (2) MR52 4 Readers | 16 Inputs | 12 Outputs

Size and Weight:

• 24.00"H x 16.00"W x 4.50"D | 41 lbs.

BluCHIP 4R/16I/12O-E4M1L

Recommended board layout



Kit Includes

MFG Part #	BluBØX Order #	QTY	Description
MR52	120-2500	2	Mercury MR52: Two door controller & auxiliary I/O 12/24VDC
E4ML-SK-4T	577-3040	1	BluBØX E4ML-SK-4T Speed Kit: Four board precut DC power, RS485 and lock trigger wiring kit
FP0150-B100C8PD8PE4M1	670-1475	1	LifeSafety Power: Eight door power supply w/ power distribution, includes enclosure

Expansion Options

MFG Part #	BluBØX Order #	QTY	Description
MR52	120-2500	2	Mercury MR52: Two door controller & auxiliary I/O 12/24VDC

Ordering Information

BluBØX Order #	Description	
752-8350	Mercury MR52 Four Reader/Sixteen Input/Twelve Output Addition System w/ Managed Lock Power for Eight Doors	

BluBØX: Security Re-Imagined www.blub0x.com e. info@blub0x.com p. (844) 425-8209 FOLLOW US ON 🎾 in BluBØX Security, Inc. is a manufacturer and service provider of web-cloud based physical security products. Its BluSKY service delivers enterprise class unified access control, alarm management, video surveillance, biometrics and visitor management on any device, anywhere, any time. Its BluCHIP open hardware platform provides industry standard components and a proprietary line of fully integrated multi-factor, multi-biometric Person Readers.