




BluCHIP 1501-2R/4I/4O-E4M1L

Mercury EP1501 Two Reader/Four Input/Four Output System w/ Managed Lock Power for Eight Doors

The BluCHIP 1501-2R/4I/4O-E4M1L is a unified Two Reader/Four Input/Four Output System w/ Managed Lock Power for Eight Doors and expansion space to support six additional readers. The kit is configured with space to add backup battery and utilizes an FPO power supply to generate 24VDC and a B100 to generate 12VDC. It includes a Mercury EP1501 and a Mercury MR50 board, a locking eight door enclosure with tamper, power supply and wiring speed kit. Local managed lock power is included. It is expandable to eight readers with three Mercury MR52 boards. Remote management and reporting of power supply and battery health are available through BluSKY Power Diagnostics.



System Features

FPO offline power supply

- 120 or 230 VAC input
- 12 and 24 VDC outputs
- On board Fire Alarm Interface
- Continuous and resettable DC

Distributed output module

- Four, controlled fused at 3A each
- Eight, auxiliary Class II P limited at 2.5A each

Expansion options

- Increased power, multiple voltages
- Additional distribution outputs
- Power management

Enclosure Features

Labor saving design

- Unified power and security in one enclosure
- Pre-wired power section
- Removeable backplate simplifies installs
- Speed kit is included for power and data wiring
- Includes mounting studs on door to add additional I/O boards

Additional benefits

- Wire management room
- 4.5" enclosure depth fits battery set
- Tamper switch, lock, dual key set standard
- Mounting hardware for access boards included

Specifications

Input Power:

- Input 120/230VAC 50/60Hz | 200 Watts
- Overload and short circuit protection
- Over temperature protection
- Polarized AC power supply disconnect

Output Power:

- 150W Total Output Power | 12VDC/6A or 24VDC/6A
- 5-18VDC @ 4A Max. | FPO Board Outputs: Continuous (DC1), Resettable (DC2)
- 8 Lock Outputs, 8 Auxiliary Outputs, Class 2 PL @ 2.5A each
- 120mV Output Voltage Ripple | System Efficiency: 88% | System BTU Rating: 66 BTU/Hr

Battery Charging:

- Independent built-in 2A (FPO150) Charger for sealed lead-acid or gel type batteries
- Microprocessor dual rate charging of 12 or 24V battery sets
- Automatic switchover to standby battery when AC fails
- Zero voltage drop when switched over to battery backup

Regulatory Compliance:

- UL294, UL603, UL864, UL1076, UL1481, UL2044, UL2572, ULC S318, ULC S319, ULC S527, CSA C22.2 #107.1, FCC Part 15, CSFM Approved

Access Panel:

- (1) EP1501, (1) Mercury MR50
2 Readers | 4 Inputs | 4 Outputs

Size and Weight:

- 24.00"H x 20.00"W x 4.50"D | 41 lbs.

Recommended board layout



Kit Includes

MFG Part #	BluBØX Order #	QTY	Description
EP1501	120-1000	1	Mercury EP1501: One door DB controller Ethernet PoE/12V
MR50	120-2300	1	Mercury MR50: One door controller 12/24VDC
E4ML-SK-5T	577-3045	1	BluBØX E4ML-SK-5T Speed Kit: Five board precut DC power, RS485 and lock trigger wiring kit
EP1501-MR50	640-1400	1	BluBØX EP1501-MR50 Bracket
FPO150-B100C8PD8PE4M1	670-1475	1	LifeSafety Power: Eight door power supply w/ power distribution, includes enclosure

Expansion Options Table

MFG Part #	BluBØX Order #	QTY	Description
MR52	120-2500	3	Mercury MR52: Two door controller & auxiliary I/O 12/24VDC

Ordering Information

BluBØX Order #	Description
752-2400	Mercury EP1501 Two Reader/Four Input/Four Output System w/ Managed Lock Power for Eight Doors

BluBØX: Security Re-Imagined

www.blub0x.com

e. info@blub0x.com

p. (844) 425-8209

FOLLOW US ON  

BluBØX Security, Inc. is a manufacturer and service provider of web-cloud based physical security products. Its BluSKY service delivers enterprise class unified access control, alarm management, video surveillance, biometrics and visitor management on any device, anywhere, any time. Its BluCHIP open hardware platform provides industry standard components and a proprietary line of fully integrated multi-factor, multi-biometric Person Readers.